

Safety Data Sheet

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

MD-Klebstoffentferner

UFI: AR2R-6A4F-M00M-1Y5Q

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.3. Details of the supplier of the safety data sheet

Company name: Marston-Domsel GmbH
Street: Bergheimer Str. 15
Place: 53909 Zülpich
Telephone: +49 (0) 22 52 94 15 - 0 Telefax: +49 (0) 22 52 17 44
e-mail: info@marston-domsel.de
Contact person: Qualitätsmanagement
e-mail: QM@marston-domsel.de
Internet: www.marston-domsel.de

1.4. Emergency telephone number:

Emergency CONTACT (24-Hour-Number): GBK GmbH +49 (0)6132-84463

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No 1272/2008

Flam. Liq. 2; H225
Eye Irrit. 2; H319
STOT SE 3; H336

Full text of hazard statements: see SECTION 16.

2.2. Label elements

Regulation (EC) No 1272/2008

Hazard components for labelling

acetone; propan-2-one; propanone
ethyl acetate

Signal word: Danger

Pictograms:



Hazard statements

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.
P102 Keep out of reach of children.
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P370+P378 In case of fire: Use extinguishing powder to extinguish.
P403+P235 Store in a well-ventilated place. Keep cool.
P501 Dispose of contents/container to an appropriate recycling or disposal facility.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 2 of 11

Special labelling of certain mixtures

EUH066 Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	Classification (Regulation (EC) No 1272/2008)			
67-64-1	acetone; propan-2-one; propanone			50 - < 100 %
	200-662-2	606-001-00-8	01-2119471330-49	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			
141-78-6	ethyl acetate			25 - < 50 %
	205-500-4	607-022-00-5	01-2119475103-46	
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 EUH066			

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Conc. Limits, M-factors and ATE		
67-64-1	200-662-2	acetone; propan-2-one; propanone	50 - < 100 %
	inhalation: LC50 = 76 mg/l (vapours); dermal: LD50 = 7400 mg/kg; oral: LD50 = 5800 mg/kg		

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

When in doubt or if symptoms are observed, get medical advice. Take off immediately all contaminated clothing and wash it before reuse.

After inhalation

Remove casualty to fresh air and keep warm and at rest. If unconscious but breathing normally, place in recovery position and seek medical advice. If experiencing respiratory symptoms: Call a doctor.

After contact with skin

Take off contaminated clothing and wash it before reuse. Gently wash with plenty of soap and water. In case of skin reactions, consult a physician.

After contact with eyes

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Protect uninjured eye.

After ingestion

Rinse mouth thoroughly with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person or a person with cramps. Get medical advice/attention if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Dyspnoea
Headache
Dizziness
Dizziness



Safety Data Sheet

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 3 of 11

Nausea

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Water spray jet, Carbon dioxide (CO₂), Foam, Extinguishing powder.
Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

Highly flammable. Vapours can form explosive mixtures with air.
In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO₂))

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus. Full protection suit.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Remove all sources of ignition. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes.

For non-emergency personnel

Provide adequate ventilation. Use personal protection equipment.

For emergency responders

Personal protection equipment: see section 8

6.2. Environmental precautions

Do not allow uncontrolled discharge of product into the environment. Explosion risk.

6.3. Methods and material for containment and cleaning up

For containment

Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal. Ventilate affected area.

Other information

Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7

Personal protection equipment: see section 8

Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 4 of 11

gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking. Take precautionary measures against static discharges. Vapours can form explosive mixtures with air.

Advice on general occupational hygiene

Remove contaminated, saturated clothing immediately. Draw up and observe skin protection programme. Wash hands and face before breaks and after work and take a shower if necessary. When using do not eat, drink, smoke, sniff.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep locked up. Store in a place accessible by authorized persons only. Provide adequate ventilation as well as local exhaust at critical locations. Keep in a cool, well-ventilated place. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Hints on joint storage

Do not store together with: Oxidizing agent. Pyrophoric or self-heating substances.

7.3. Specific end use(s)

Solvent

SECTION 8: Exposure controls/personal protection**8.1. Control parameters****Occupational exposure limit values**

CAS No	Name of agent	ppm	mg/m ³	fib/cm ³	Category	Origin
67-64-1	Acetone	500	1210		TWA (8 h)	
141-78-6	Ethyl acetate	200	734		TWA (8 h)	
		400	1468		STEL (15 min)	

DNEL/DMEL values

CAS No	Name of agent	Exposure route	Effect	Value
67-64-1	acetone; propan-2-one; propanone			
	Consumer DNEL, long-term	oral	systemic	62 mg/kg bw/day
	Worker DNEL, long-term	dermal	systemic	186 mg/kg bw/day
	Consumer DNEL, long-term	dermal	systemic	62 mg/kg bw/day
	Worker DNEL, acute	inhalation	local	2420 mg/m ³
	Worker DNEL, long-term	inhalation	systemic	1210 mg/m ³
	Consumer DNEL, long-term	inhalation	systemic	200 mg/m ³

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 5 of 11

PNEC values

CAS No	Name of agent	
	Environmental compartment	Value
67-64-1	acetone; propan-2-one; propanone	
	Freshwater	10,6 mg/l
	Marine water	1,06 mg/l
	Freshwater sediment	30,4 mg/kg
	Marine sediment	3,04 mg/kg
	Micro-organisms in sewage treatment plants (STP)	100 mg/l
	Soil	29,5 mg/kg

8.2. Exposure controls**Appropriate engineering controls**

Provide adequate ventilation as well as local exhaust at critical locations.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear eye/face protection. (EN 166)

Hand protection

Wear suitable gloves. (EN ISO 374)

Suitable material: Butyl caoutchouc (butyl rubber)
 Thickness of the glove material: $\geq 0,7$ mm
 Permeation time (maximum wear duration): ≥ 480 min.

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves.

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection. (EN 14387) Filter type: A

Thermal hazards

Flame-retardant protective clothing. Wear anti-static footwear and clothing

Environmental exposure controls

Avoid release to the environment.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties**

Physical state:	Liquid	
Colour:	colourless	
Odour:	like: Solvent	
Odour threshold:	not determined	
Melting point/freezing point:		not determined

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 6 of 11

Boiling point or initial boiling point and boiling range:	56 °C
Flammability:	Highly flammable liquid and vapour.
Lower explosion limits:	2,1 vol. %
Upper explosion limits:	13 vol. %
Flash point:	approx. -19 °C
Auto-ignition temperature:	460 °C
Decomposition temperature:	not determined
pH-Value:	not determined
Viscosity / kinematic:	not determined
Water solubility:	partially miscible
Solubility in other solvents	not determined
Partition coefficient n-octanol/water:	not determined
Vapour pressure: (at 20 °C)	247 hPa
Density (at 20 °C):	0,82 g/cm ³
Relative vapour density:	not determined
Particle characteristics:	not applicable

9.2. Other information**Information with regard to physical hazard classes****Explosive properties**

The product is not: Explosive. Vapours can form explosive mixtures with air.

Other safety characteristics

Solvent content: 100,00 %

Further Information

No information available.

SECTION 10: Stability and reactivity**10.1. Reactivity**

Highly flammable.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

Vapours can form explosive mixtures with air.

10.4. Conditions to avoid

Keep away from sources of heat (e.g. hot surfaces), sparks and open flames.

10.5. Incompatible materials

Oxidizing agent. Pyrophoric or self-heating substances.

10.6. Hazardous decomposition products

In case of fire may be liberated: Pyrolysis products, toxic (Carbon monoxide, Carbon dioxide (CO₂))

SECTION 11: Toxicological information**11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity**

Based on available data, the classification criteria are not met.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 7 of 11

CAS No	Chemical name				
	Exposure route	Dose	Species	Source	Method
67-64-1	acetone; propan-2-one; propanone				
	oral	LD50 mg/kg	5800	Rat	Manufacturer
	dermal	LD50 mg/kg	7400	Rabbit	Manufacturer
	inhalation (4 h) vapour	LC50	76 mg/l	Rat	Manufacturer

Irritation and corrosivity

Causes serious eye irritation.

Skin corrosion/irritation: Based on available data, the classification criteria are not met.

Sensitising effects

Based on available data, the classification criteria are not met.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

May cause drowsiness or dizziness. (acetone; propan-2-one; propanone; ethyl acetate)

STOT-repeated exposure

Repeated exposure may cause skin dryness or cracking.

Aspiration hazard

Based on available data, the classification criteria are not met.

Information on likely routes of exposure

oral, dermal, inhalative, Eye contact

11.2. Information on other hazards**Endocrine disrupting properties**

This product does not contain a substance that has endocrine disrupting properties with respect to humans as no components meets the criteria.

SECTION 12: Ecological information**12.1. Toxicity**

Based on available data, the classification criteria are not met.

12.2. Persistence and degradability

The product has not been tested.

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
67-64-1	acetone; propan-2-one; propanone	-0,24

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 8 of 11

Further information

Avoid release to the environment.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Disposal recommendations**

Do not allow to enter into surface water or drains. Dispose of waste according to applicable legislation.

The allocation of waste identity numbers/waste descriptions must be carried out according to the EEC, specific to the industry and process.

List of Wastes Code - residues/unused products

070104 WASTES FROM ORGANIC CHEMICAL PROCESSES; wastes from the manufacture, formulation, supply and use (MFSU) of basic organic chemicals; other organic solvents, washing liquids and mother liquors; hazardous waste

List of Wastes Code - contaminated packaging

150110 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); packaging containing residues of or contaminated by hazardous substances; hazardous waste

Contaminated packaging

Wash with plenty of water. Completely emptied packages can be recycled.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (Acetone, Ethyl acetate)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640D
Limited quantity:	1 L
Excepted quantity:	E2
Transport category:	2
Hazard No:	33
Tunnel restriction code:	D/E

Inland waterways transport (ADN)

14.1. UN number or ID number:	UN 1993
14.2. UN proper shipping name:	FLAMMABLE LIQUID, N.O.S. (Acetone, Ethyl acetate)
14.3. Transport hazard class(es):	3
14.4. Packing group:	II
Hazard label:	3



Classification code:	F1
Special Provisions:	274 601 640D

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 9 of 11

Limited quantity: 1 L
 Excepted quantity: E2

Marine transport (IMDG)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHYLACETATE)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: 274
 Limited quantity: 1 L
 Excepted quantity: E2
 EmS: F-E, S-E

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number or ID number: UN 1993
14.2. UN proper shipping name: FLAMMABLE LIQUID, N.O.S. (ACETONE, ETHYLACETATE)
14.3. Transport hazard class(es): 3
14.4. Packing group: II
 Hazard label: 3



Special Provisions: A3
 Limited quantity Passenger: 1 L
 Passenger LQ: Y341
 Excepted quantity: E2
 IATA-packing instructions - Passenger: 353
 IATA-max. quantity - Passenger: 5 L
 IATA-packing instructions - Cargo: 364
 IATA-max. quantity - Cargo: 60 L

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: No

14.6. Special precautions for user

Warning: Highly flammable liquid and vapour.

14.7. Maritime transport in bulk according to IMO instruments

not applicable

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 3, Entry 40, Entry 75

2010/75/EU (VOC): 100 % (820 g/l)
 Information according to 2012/18/EU (SEVESO III): P5c FLAMMABLE LIQUIDS

National regulatory information

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 10 of 11

Employment restrictions: Observe restrictions to employment for juveniles according to the 'juvenile work protection guideline' (94/33/EC).

Water hazard class (D): 1 - slightly hazardous to water

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information**Abbreviations and acronyms**

CLP: Classification, labelling and Packaging

REACH: Registration, Evaluation and Authorization of Chemicals

GHS: Globally Harmonised System of Classification, Labelling and Packaging of Chemicals

UN: United Nations

CAS: Chemical Abstracts Service

DNEL: Derived No Effect Level

DMEL: Derived Minimal Effect Level

PNEC: Predicted No Effect Concentration

ATE: Acute toxicity estimate

LC50: Lethal concentration, 50%

LD50: Lethal dose, 50%

LL50: Lethal loading, 50%

EL50: Effect loading, 50%

EC50: Effective Concentration 50%

ErC50: Effective Concentration 50%, growth rate

NOEC: No Observed Effect Concentration

BCF: Bio-concentration factor

PBT: persistent, bioaccumulative, toxic

vPvB: very persistent, very bioaccumulative

ADR: Accord européen sur le transport des marchandises dangereuses par Route

(European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Regulations concerning the international carriage of dangerous goods by rail

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways (Accord européen relatif au transport international des marchandises dangereuses par voies de navigation intérieures)

IMDG: International Maritime Code for Dangerous Goods

EmS: Emergency Schedules

MFAG: Medical First Aid Guide

IATA: International Air Transport Association

ICAO: International Civil Aviation Organization

MARPOL: International Convention for the Prevention of Marine Pollution from Ships

IBC: Intermediate Bulk Container

VOC: Volatile Organic Compounds

SVHC: Substance of Very High Concern

For abbreviations and acronyms, see: ECHA Guidance on information requirements and chemical safety assessment, chapter R.20 (Table of terms and abbreviations).

Classification for mixtures and used evaluation method according to Regulation (EC) No 1272/2008 [CLP]

Classification	Classification procedure
Flam. Liq. 2; H225	On basis of test data
Eye Irrit. 2; H319	Calculation method
STOT SE 3; H336	Calculation method

Relevant H and EUH statements (number and full text)

H225 Highly flammable liquid and vapour.
H319 Causes serious eye irritation.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

MD-Klebstoffentferner

Revision date: 28.07.2023

Product code: MRM

Page 11 of 11

H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.

Further Information

The information is based on the present level of our knowledge. It does not, however, give assurance of product properties and establishes no contract legal rights. The receiver of our product is singularly responsible for adhering to existing laws and regulations.

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)